



Features and Benefits

- Accurately measures particles at 0.100 μm
- 0.100 to 10.0 μm size range
- Up to eight channels of simultaneous data
- 28.3 L/min (1.0 CFM) flow rate
- Complies with all requirements of ISO 21501-4
- Best choice for testing Class 1 and 2 Clean Rooms
- Utilizes enhanced HeNe laser
- Highly repeatable and reliable measurements/data
- 10,000 sample record storage, 999 locations
- Ethernet, USB, and pulse outputs
- Industry's loudest audible alarm
- Allows storage and recall of specific tests/recipes
- Displays up to three environmental parameters
- Stainless steel enclosure
- Seamless integration with M32-01 manifold
- Clean room classification down to ISO Class 1

AERO TRAK™ Portable Particle Counter Model 9110

The TSI AERO TRAK™ 9110 Portable Particle Counter offers an accurate measurement of particles down to 0.100 μm ! This is made possible utilizing a patented HeNe laser technology that is low maintenance with an enhanced signal to noise ratio. The Model 9110 is ideal for performing ISO-14644-1 classifications for Class 1 and Class 2 clean rooms. This instrument is designed for clean room monitoring, process tool monitoring, and filter test applications.

The Model 9110 can generate pass/fail reports for ISO 14644-1. This product can be used as a stand-alone particle counter or integrated into a facility monitoring system like FMS 5.

The Model 9110 complies with all the stringent requirements set forth in ISO 21501-4. It is calibrated with NIST traceable PSL spheres using TSI's world-class Classifier and Condensation Particle Counters, the recognized standard for particle measurements. Backed with a standard two-year warranty and TSI commitment for superior service and support, there are no other portable 0.100 μm particle counters like it on the market today.



Specifications

Model 9110

AEROTRAK™ Portable Particle Counter

Features	9110
Size Range	0.100 to 10.0 µm
Particle Channel Sizes	9110-01: 0.10, 0.15, 0.2, 0.25, 0.3, 0.5, 1.0, 5.0 µm
Size Resolution	<15% @ 0.2 µm (per ISO 21501-4)
Counting Efficiency	50% at 0.100 µm; 100% for particles >0.15 µm (per ISO 21501-4 and JIS)
Concentration Limit	>40,000/ft ³ at 5% coincidence loss
Light Source	Enhanced active cavity HeNe laser
Zero Count	<1 count per 5 minutes (per ISO 21501-4 and JIS)
Flow Rate	28.3 L/min (1.0 CFM) ±5% accuracy (meets ISO 21501-4 and JIS B9921)
Flow Rate Control	Electronic, automatic closed loop (patented* flow control technology)
Calibration	NIST traceable using TSI calibration system
Calibration Frequency	Recommended minimum of once per year
Sampling Modes	Manual, automatic, beep; cumulative/differential; count or concentration
Sampling Time	1 second to 99 hours
Sampling Frequency	1 to 9999 cycles or continuous
Exhaust	Internal HEPA filter
Communication Mode	Modbus® TCP over Ethernet or USB
Data Storage	10,000 sample records: includes date, time, eight particle channels, flow, ID, and sample volume; transferable via USB data download or TRAKPro™ Lite software
Audible Alarm	Built-in; >85 dB at 1 meter (adjustable)
Status Indicator	Low battery, flow, laser
Alarm Output	Dry contacts, normally closed when alarm is engaged
Alarm Limits	Programmable for all particle channels
Display	VGA 14.5-cm touch screen display
Languages	English, German, French, Spanish, Japanese, Chinese (simplified), Italian
Software	Compatible with TRAKPro™ Lite and FMS 5 software

Features	9110
Printer	Built-in thermal printer (also available without printer)
Printer Output	Prints in all available languages
Environmental Sensor Interface	Supports TSI Probe Models: 960, 962, 964, 966 (air velocity/temp/RH) and Temp/RH probe
Unit ID	Configurable IP address
Security	2-level password protection to lock out usage and configuration
Location ID	Up to 999 Locations; 16 characters long
Reports	Provides Pass/Fail on ISO 14644-1, and FS209E reports
External Surface	Stainless steel
Dimension (H x W x D)	23.6 cm x 20.6 cm x 52.2 cm
Weight	11.14 kg without battery; 12.70 kg with battery
Power	110 to 240 VAC, 50 to 60 Hz universal power supply
Battery	Removeable/rechargeable Li-Ion battery, up to four batteries
Battery Life	Up to 4 hours continuous use
Recharge Time	3.5 hours (when idle)
Standards	ISO 21501-4, CE, JIS B9921
Warranty	Two years, extended warranties available
Operating Range	10° to 35°C, 20% to 95% noncondensing
Storage Range	0° to 50°C, up to 98% RH noncondensing
Included Accessories	Printed QuickStart guide, operating manual on CD, power supply, battery, barbed inlet, isokinetic probe, tripod, tubing, printer paper, USB cable and TRAKPro™ Lite software
Optional Accessories	Electronic filter scanning probe, basic filter scanning probe, TSI velocity probes, Temp/RH probe, additional battery, dual port external battery charger, purge filter, isokinetic inlets, sample tubing

*Patent Number 6,167,107

Specifications are subject to change without notice. TSI, the TSI logo, AEROTRAK, and TRAKPro are trademarks of TSI Incorporated. Modbus is a registered trademark of Modicon, Inc.

TSI Incorporated - 500 Cardigan Road, Shoreview, MN 55126-3996 USA

USA	Tel: +1 800 874 2811	E-mail: info@tsi.com	Website: www.tsi.com
UK	Tel: +44 149 4 459200	E-mail: tsiuk@tsi.com	Website: www.tsiinc.co.uk
France	Tel: +33 491 11 87 64	E-mail: tsifrance@tsi.com	Website: www.tsiinc.fr
Germany	Tel: +49 241 523030	E-mail: tsigmbh@tsi.com	Website: www.tsiinc.de
India	Tel: +91 80 41132470	E-mail: tsi-india@tsi.com	
China	Tel: +86 10 8251 6588	E-mail: tsibeijing@tsi.com	
Singapore	Tel: +65 6595 6388	E-mail: tsi-singapore@tsi.com	



TRUST. SCIENCE. INNOVATION.

Contact your local TSI Distributor or visit our website www.tsi.com for more detailed specifications.